

TOWA

Price Computing Scale OZ-V/OZ-L Series

*OZ-15L
Table top type*



*OZ-15V
Tower type*

 **TOWA MECCS CORPORATION**

Price Computing Scale **OZ-V/OZ-L Series**

Versatile, yet Easy to Operate!

Features

- Shock & overload protection for a long operating life
- Splashproof keyboard & display
- Battery operation for use in areas without power
- Efficient & intuitive operation speeds checkout times
- Stores prices for up to 30 items(OZ-V/VA)
- Stores prices for up to 12 items(OZ-L)
- Large wide angle display makes reading easy under all conditions
- Push button and keyboard tare entry
- Large stainless steel weighing pan resists damage and corrosion
- Optional RS-232C interface for Cash Register and PC connection
- Select from AC power, replaceable batteries or rechargeable battery



Rear View (OZ-L Series)

OZ-V:
Tower type



OZ-L:
Table top type



Specifications

Model	OZ-15V/15VA	OZ-30V/30VA	OZ-15L	OZ-30L
Capacity/Resolution	15kg×5g	30kg×10g	15kg×5g	30kg×10g
Non-linearity	±5g	±10g	±5g	±10g
Repeatability/Std. Dev.	5g	10g	5g	10g
Display	Vacuum Fluorescent Display – OZ-V/VA Liquid Crystal Display – OZ-L			
Display Indications	Weight – 5 digits Price – 7 digits Unit Price – 6 digits			
Pan Size	300(W) × 280(D) mm / 11.81(W) × 11.02(D) inches			
Weight(Approximately)	5.5kg		4.5kg	
Power	OZ-V – AC power only OZ-L – AC adapter & dry battery(6×R20P/LR20/ "D") OZ-VA – AC adapter & NiCd rechargeable battery(Optional)			
Battery Life(Approximately)	300 hours with manganese type cells 500 hours with alkaline type cells			
Operating Temperature	– 10℃ ~ 40℃ (14° F ~ 104° F) RH less than 85%			
Physical Dimensions	465(W) × 425(D) × 460(H) mm 18.31(W) × 16.73(D) × 18.11(H) inches		330(W) × 425(D) × 108(H) mm 12.99(W) × 16.73(D) × 4.25(H) inches	

Specifications subject to change for improvement without notice.

Option

Serial Interface (RS-232C)
Rechargeable Battery Pack

TOWA MECCS CORPORATION

5-5, Hongo 3-chome, Bunkyo,
Tokyo 113-0033, Japan
Tel. 81-3-5684-5681 Fax. 81-3-5684-5791
<http://www.towa-meccs.com>

Sold and Serviced by